

Amendments to the Claims

This listing of claims will replace all prior versions, and listing, of claims in the application.

Listing of Claims:

1. (Currently Amended) ~~A simulator system comprising a manikin and a medical device, the simulator system for simulating the use and movement of a the medical device in a simulated body cavity or lumen of a the manikin and further comprising: patient, comprising:~~
 - (a) ~~a the medical device comprising having~~ a first end for manipulation by a first user and a portion ~~comprising having~~ a second end insertable into a simulated body cavity or body lumen in a manikin;
 - (b) ~~the a manikin includes comprising an interface device configured to receive for receiving the medical device portion having comprising the second end and to interface for interfacing with a the simulated body cavity or lumen within the manikin, wherein the interface comprises device includes an active directional force feedback mechanism that exerts for exerting a directional force on the medical device in response to a feedback signal received by the force feedback mechanism; and~~
 - (c) a computational engine embodying physically based modeling using finite element methodology, the computational engine simulating interactions between the medical device and body cavity or lumen, ~~the interactions relating to the manipulation of the medical device by the first user; and~~

wherein the system ~~computational engine models~~ interactions between the medical device and the body cavity or lumen in three-dimensions, computes forces that would arise from interactions between the medical device and body cavity or lumen and ~~outputs feedback signals corresponding to the computer forces to the active directional force feedback mechanism so as to thereby feedback feeds back said computed forces to the user.~~

2. (Currently Amended) The ~~system~~simulator system according to claim 1, wherein the active directional force feedback mechanism ~~is configured so as to provide~~ provides resistance to forward motion but enables free reverse motion in response to the feedback signal.
3. (Currently Amended) The ~~system~~simulator system according to claim 1, wherein the active directional force feedback mechanism comprises a rolling element coupled to the ~~medical device portion having of the device comprising the second end and wherein an internal surface of the simulated cavity or lumen in the manikin comprises~~includes an oblique slot for receiving the rolling element.
4. (Currently Amended) The ~~system~~simulator system according to claim 3, wherein, in response to a feedback signal, forward movement of the ~~medical device~~ second end causes the rolling element to be received by the slot, thereby causing resistance to further forward motion.
5. (Currently Amended) The ~~system~~simulator system according to claim 4, wherein ~~the active directional force feedback mechanism includes a motor, where the motor controls movement of the rolling element.~~
6. (Currently Amended) The ~~system~~simulator system according to claim 1, further comprising a tactile feedback mechanism.
7. (Currently Amended) The ~~system~~simulator system according to claim 6, wherein the tactile feedback mechanism ~~is responsive to inputs corresponding to simulated forces being exerted on the medical device, wherein the tactile feedback mechanism is configured so as to provide~~ provides continuous oscillatory feedback to a user holding the

medical device to simulate medical device motion induced by the simulated forces being exerted on the medical device.

8. (Currently Amended) The ~~system~~simulator system according to claim 7, wherein the ~~tactile feedback mechanism includes a continuously rotating motor and wherein the continuous vibrational oscillatory feedback is provided through a the continuously rotating motor in operable contact communication with the medical device portion including of the device comprising the second end.~~
9. (Currently Amended) The ~~system~~simulator system according to claim 1, ~~further comprising a user display and a tracking device for continuously tracking wherein a position of at least the medical device second end of the medical device relative to the simulated body cavity or lumen within the manikin, wherein the user display displays the simulated body cavity or lumen and the medical device based on its relative position and movement is continuously tracked.~~
10. (Currently Amended) The ~~system~~simulator system according to claim 9, wherein the ~~tracking device medical device~~ comprises an encoder for tracking the translation of the medical device and an encoder for tracking the rotation of the medical device, ~~the translation and rotational encoders being embodied in the medical device.~~
11. (Currently Amended) The ~~system~~simulator system according to claim 9, wherein the ~~manikin further tracking device~~ comprises an optical tracking unit ~~embodied in the manikin, the optical tracking unit including comprising~~ a light source, a signal processing circuit, and one or more optical sensors, wherein the ~~optical tracking unit is placed within the interface device so as to be in~~ optical communication with the medical device when it is inserted into the ~~simulated~~ cavity or lumen.

12. (Currently Amended) The ~~systemsimulator system~~ according to claim 11, wherein light from the light source reflects ~~on~~ from the medical device when ~~it is~~ inserted and wherein the reflected light is received by the one or more optical sensors.
13. (Currently Amended) The ~~systemsimulator system~~ according to claim 12, wherein changes in reflected light received by the one or more sensors is detected and outputs are provided to the computational engine, by the system, and wherein, in response to these ~~outputs, the computational engine~~ this detection, the system simulates movement of the medical device in real-time and displays such simulated movement on the user display.
14. (Currently Amended) The ~~systemsimulator system~~ according to claim 12, wherein two optical sensors are provided which are perpendicular to one another.
15. (Currently Amended) The ~~systemsimulator system~~ according to claim 12, wherein the optical tracking unit is configured in the form of a rail along which the medical device can move.
16. (Currently Amended) The ~~systemsimulator system~~ according to ~~claim 10~~ claim 9, wherein:
one or more additional medical devices are inserted into the interface device, wherein each of said one or more additional medical devices includes comprising a first end for manipulation by a user and a portion comprising including a second end for insertion into the simulated body cavity or body lumen, are inserted into the interface and wherein
the position relative to the simulated body cavity or lumen of each of the one or more additional medical device inserted into the interface device is independently trackedmonitored, and

the display displays the relative position and movement of each of the one or more additional medical devices and the simulated body cavity or lumen.

17. (Currently Amended) The ~~system~~simulator system according to claim 16, wherein the ~~medical device and the one or more additional medical devices are each~~ selected from the group consisting of a catheter, guidewire, endoscope, laparoscope, bronchoscope, stent, coil, balloon, a balloon-inflating device, a surgical tool, a vascular occlusion device, optical probe, a drug delivery device, and combinations thereof.
18. (Currently Amended) The ~~system~~simulator system according to claim 1, further comprising ~~includes a~~ table for placing the manikin thereon, wherein the table comprises a processor connectable to ~~the a~~ network.
19. (Currently Amended) The ~~system~~simulator system according to ~~claim 18~~claim 1, wherein the ~~simulator system~~ further comprises at least one first user device being ~~operably coupled to the computational engine, connectable to the network, wherein the first user device includes comprising a first display interface device that displays for displaying a three-dimensional representation of a the simulated body cavity or lumen of a patient.~~
20. (Currently Amended) The ~~system~~simulator system according to claim 19, wherein the first display ~~device interface~~ further displays a three-dimensional representation of ~~the a medical device along with the simulated body cavity or lumen corresponding to a medical device which is interfaced with the manikin and wherein the system computational engine simulates on the display the movement of the medical device within the simulated body cavity or lumen of the manikin in real-time when as a first user manipulates the medical~~

~~device in the simulated body cavity or lumen within interfaced with the manikin and causes such simulations to be displayed on the first display device.~~

20. (Canceled)
21. (Currently Amended) The ~~systemsimulator system~~ according to claim 19, further comprising a simulated scanning display ~~that displays an image that is representative of~~ for displaying ~~one of~~ a two-dimensional scanned image ~~or a three-dimensional reconstructed scanned image of~~ the simulated body cavity or lumen.
22. (Currently Amended) The ~~systemsimulator system~~ according to claim 21, ~~further comprising a simulated scanning device and~~ wherein the simulated scanning display is part of ~~a the~~ simulated scanning device.
23. (Currently Amended) The ~~systemsimulator system~~ according to claim 22, wherein the simulated scanning device is simulating ~~one of~~ an x-ray imaging system, ~~an MRI imaging system or an ultrasonic imaging system.~~
24. (Currently Amended) The ~~systemsimulator system~~ according to claim 22, wherein the simulated scanning device and scanning display are coupled to a movable C-arm ~~of an x-ray imaging system~~ within scanning distance of the manikin.
25. (Currently Amended) The ~~systemsimulator system~~ according to claim 1, further comprising a re-configurable control panel for performing one or more of: image acquisition selection; image display; manipulating a table on which the manikin is placed; manipulating the position of a simulated scanning device relative to the manikin; and control of one or more shutter devices for limiting a field of view of ~~a the~~ simulated scanning device ~~when~~ placed within scanning distance of the manikin.

26. (Currently Amended) The ~~system~~simulator system according to claim 1 or 20, further comprising a monitoring station, the monitoring station ~~comprising including~~ a second user device ~~connectable to the network and comprising~~ a second display interface for enabling a second user to monitor the movement of the medical device within the simulated body cavity or lumen.
27. (Currently Amended) The ~~system~~simulator system according to claim 26, wherein the second display interface of the monitoring station displays selectable options enabling the second user to select or change one or more anatomical and/or physiological parameters of the simulated body cavity or lumen, and wherein the selection causes ~~a~~ the three-dimensional image of the simulated body cavity or lumen being displayed to ~~a~~ the first user to change to reflect the changed anatomical and/or physiological parameters.
28. (Currently Amended) The ~~system~~simulator system according to claim 20, wherein the ~~system computational engine is operably coupled connectable to a database of patient images and/or medical data so the patient images and/or medical data can be obtained and displayed to the first user.~~
29. (Currently Amended) The ~~system~~simulator system according to claim 26, wherein the ~~system computational engine is operably coupled connectable to a database of patient images and/or medical data so the patient images and/or medical data can be obtained and displayed to the first user.~~
30. (Currently Amended) The ~~system~~simulator system according to claim 28, wherein the patient images comprise images of a body cavity or lumen from a patient affected by a pathology.

31. (Currently Amended) The ~~systemsimulator system~~ according to claim 29, wherein the patient images comprise images of a body cavity or lumen from a patient affected by a pathology.
32. (Currently Amended) The ~~systemsimulator system~~ according to claim 22, further comprising at least one foot-activation switch for activating or collimating the simulated scanning device, image display or table movement.
33. (Currently Amended) The ~~systemsimulator system~~ according to claim 28, wherein the ~~first user device is configured so as to allow the first user to display interface provides access to the database of patient images and/ or medical data, and wherein, in response to said accessing, the requested system displays an image and/ or medical data is displayed on the first user display device interface.~~
34. (Currently Amended) The ~~systemsimulator system~~ according to ~~claim 29, claim 28,~~ wherein the ~~second user display interface provides is configured so as to allow the second user to access to the database of patient images and/ or medical data, and wherein, in response to said accessing, the system displays an requested image and/ or medical data is displayed on the second user display interface.~~
35. (Currently Amended) The ~~systemsimulator system~~ according to claim 33, further ~~comprising a monitoring station that includes a second user device and a second display interface to enable a second user to monitor the movement of the medical device within the simulated body cavity or lumen. and wherein the second user display interface provides is configured so as to allow the second user to access to the database of patient images and/ or medical data, and wherein, in response to said accessing, the system displays an requested image and/ or medical data are displayed on the second user display interface.~~

36. (Currently Amended) The ~~systemsimulator system~~ according to claim 35, wherein the second user-display interface provides a selectable option enabling a second user to display the image displayed on the second user-display interface, on the first user's display ~~deviceinterface~~.
37. (Currently Amended) The ~~systemsimulator system~~ according to claim 1, wherein the medical device is selected from the group consisting of a catheter, guidewire, endoscope, laparoscope, bronchoscope, stent, coil, balloon, a balloon-inflating device, a surgical tool, a vascular occlusion device, optical probe, a drug delivery device, and combinations thereof.

Claims 38 - 43 (Cancelled)

44. (Currently Amended) ~~The system according to claim 1; A system for simulating movement of a medical device in a body cavity or lumen of a patient, comprising:~~
- ~~_____ (a) _____ a medical device comprising a first end for manipulation by a user and a portion comprising a second end insertable into a simulated body cavity or body lumen in a manikin; and~~
- ~~_____ (b) _____ the manikin comprising an interface for receiving the portion comprising the second end and for interfacing with a simulated body cavity or lumen within the manikin, wherein the interface comprises a an active directional force feedback mechanism for exerting a directional force on the medical device in response to a feedback signal received by the force feedback mechanism; and~~
- ~~_____ (c) _____ a computational engine embodying physically based modeling using finite element methodology, the computational engine simulating interactions between the medical device and the body cavity or lumen;~~
- ~~_____ wherein the system models interactions between the medical device and the simulated body cavity or lumen in three-dimensions, computes forces that would arise from interactions~~

between the medical device and the simulated body cavity or lumen and feeds back said forces to the user; and

_____ wherein the medical device comprises a syringe that simulates fluid delivery, the syringe includes: comprising:

- a housing defining a lumen comprising an opening for delivering a fluid;
- a pushing element for pushing the fluid through the opening;
- a friction-producing element in communication with the pushing element; and
- a motor in communication with the friction-producing element and comprising a signal-receiving element,

- wherein the friction-producing element causes friction between the pushing element and a surface of the lumen of the housing upon activation by the motor in response to a signal received by the signal-receiving element, and further

- wherein the opening of the syringe is connectable to a connecting piece having a first end for receiving fluid from the opening and a second end for delivering fluid to ~~the~~ a simulated body cavity or body lumen in the manikin.

45. (Cancelled)

46. (Currently Amended) The ~~systemsimulator system~~ according to claim 1, wherein the medical device comprises a balloon-inflating device that simulates deployment of a balloon within the body cavity or lumen of the patient, the balloon-inflating device comprising:

- a delivery mechanism for controlling delivery of fluid through the balloon-inflating device to the balloon;

- a pressure sensor for monitoring pressure of a fluid delivered to the balloon by the balloon-inflating device;

an electrical pressure meter for reading pressure determined by the pressure sensor, the electrical pressure meter being connectable to a processor and for transmitting a signal corresponding to a pressure value to the processor.

47. (Currently Amended) The ~~systemsimulator system~~ according to claim 20, wherein the ~~system computational engine~~ simulates deformation of the ~~simulated~~ body cavity or lumen by the medical device.
48. (Currently Amended) The ~~systemsimulator system~~ according to claim 20, wherein the ~~system the computational engine~~ simulates an operation of a medical device selected from the group consisting of: a surgical procedure, inflation or deflation of a balloon, injection of a radioopaque material into the body cavity or lumen, and combinations thereof.
49. (Currently Amended) The ~~systemsimulator system~~ according to claim 20, wherein the ~~system computational engine~~ simulates the movement of the medical device within a blood vessel.
50. (Currently Amended) The ~~systemsimulator system~~ according to claim 49, wherein the blood vessel is ~~one of in or of an organ of the patient~~ in the brain.
51. (Currently Amended) The ~~systemsimulator system~~ according to ~~claim 49, claim 50;~~ wherein the blood vessel is in ~~one of the heart or the brain~~.

52. (Currently Amended) A method for simulating the ~~use and~~ movement of a medical device in the body cavity or lumen of a patient, ~~the method comprising the steps of:~~
 ~~providing a medical device and a simulated body cavity or body lumen within a simulacrum and an active directional force feedback mechanism that is disposed in the simulated body cavity or lumen, comprising~~
 ~~_____ wherein the provided medical device has a first end for manipulation by a first user and a portion comprising including a second end that is to be inserted into a the simulated body cavity or body lumen in a manikin and wherein the active directional force feedback mechanism is configured to create resistance to forward motion of the medical device responsive to inputted feedback signals and to allow free reverse motion,~~
 ~~_____ inserting the portion of the provided medical device into the simulated body cavity or lumen,~~
 performing physically based modeling using a finite element methodology to simulate interactions between the medical device and body cavity or lumen,
 computing forces that would arise from ~~the~~ interactions between the medical device and body cavity or lumen, and
 ~~outputting feedback signals to the wherein the simulated body cavity or lumen in the manikin comprises an active directional force feedback mechanism responsive to the computed forces thereby feeding back the computed forces to the first user, which, in response to a feedback signal creates resistance to forward motion of the medical device but allows free reverse motion and feeds back the computed forces to the user.~~
53. (Currently Amended) The method according to claim 52, further comprising ~~the step of:~~
 ~~providing a system comprising that includes:~~
 a processor in communication with the active directional force feedback mechanism; ~~and, the processor connectable to the network; and~~

a first user device ~~operably coupled to in communication with the~~
processor, the first user device comprising a first display interface for displaying a
representation of a body cavity or lumen; and for providing access to a database of
three-dimensional images of body cavities and lumens from a plurality of different
patients; and

enabling ~~a the first~~ user to select from the database a representation,
wherein in response to the selection, the representation is displayed on the first
display interface.

54. (Currently Amended) The method according to claim 53, wherein the first display
interface ~~a~~ displays a three-dimensional representation of the medical device and wherein
the system simulates the movement of the medical device within the ~~simulated body~~
cavity or lumen in real-time as a first user manipulates the medical device within the
~~simulated body cavity or lumen which is interfaced with the manikin~~.

55. (Currently Amended) The method according to claim 53 or 54, further comprising the
step of:

_____ providing a monitoring station ~~that includes comprising a~~ second display interface in
communication with the processor and the first display interface, and wherein the second
display interface provides a second user with access to the database.

56. (Currently Amended) The method according to claim 55, further comprising the steps of:
_____ ~~having wherein when a second user select selects a representation from the database, and~~
_____ ~~causing the representation to be is displayed on both the first and second display~~
interfaces.

57. (Currently Amended) The method according to claim 53, further comprising the steps of:
~~_____simulating wherein the system simulates the deformation of the simulated a-body cavity~~
or lumen in response to ~~movement manipulation of the medical device in the simulated~~
~~body cavity or lumen by the first user, and~~
~~_____displaying displays the representation of the deformation on the first display interface.~~
58. (Currently Amended) The method according to claim 53, further comprising the steps of:
~~_____performing wherein the medical device performs an operation on the simulated body~~
cavity or lumen ~~using the medical device, and~~
~~_____displaying the first display interface displays a simulation of the operation on the first~~
~~display interface.~~
59. (Currently Amended) The method according to claim 58, wherein ~~said performing~~
~~includes one of inflating or deflating the operation is inflation or deflation of a balloon~~
within the simulated body cavity or lumen.
60. (Currently Amended) The method according to claim 58, wherein ~~said performing~~
~~includes injecting the operation is injection of a radioopaque fluid within the body cavity~~
or lumen.
61. (Currently Amended) The method according to claim 52, wherein the ~~provided~~ medical
device is selected from the group consisting of a catheter, guidewire, endoscope,
laparoscope, bronchoscope, stent, coil, balloon, a balloon-inflating device, a surgical tool,
a vascular occlusion device, an optical probe, a drug delivery device, and combinations
thereof.

62. (Currently Amended) The method according to claim 54, ~~further comprising the steps of:~~
~~_____ providing one or more additional medical devices,~~
~~_____ inserting the provided wherein a first user inserts one or more additional medical devices~~
into the simulated body cavity or lumen, and
~~_____ independently monitoring and displaying the movement of each inserted medical device.~~
is independently monitored.

63. (Currently Amended) The method according to claim 52, wherein the simulated body cavity or lumen ~~further includes in the manikin further comprises a tactile feedback mechanism that is disposed therein, where the tactile feedback mechanism is configured so as to be responsive to inputted feedback signals and to provide~~ providing continuous oscillatory feedback to a first user manipulating the ~~medical medical~~ device to simulate medical device motion induced by simulated forces ~~being being~~ exerted on the medical device.

Claims 64 -73 (Cancelled)

74. (Currently Amended) A ~~simulator system comprising a medical device and a simulacrum of a patient, the simulator system for simulating use and movement of the a medical device in a simulated body cavity or lumen of the a simulacrum, and further comprising:~~
patient, comprising:

- (a) ~~the a medical device comprising having a first end for manipulation by a first user and a portion comprising including a second end insertable into the a simulated body cavity or body lumen; in a manikin;~~
- (b) ~~the simulacrum including a manikin comprising an interface device being configured to receive for receiving the medical device portion including comprising the second end and to interface for interfacing with a the simulated body cavity or lumen, within the manikin; wherein the interface device includes~~

~~comprises an active feedback mechanism that is selectively operably coupled to the medical device and which provides for providing continuous oscillatory feedback to the medical device;~~

(c) a computational engine for physically based modeling using finite element methodology, the computational engine simulating interactions between the medical device and ~~the simulated body cavity or lumen;~~ and

_____ wherein the ~~computational engine system~~ models interactions between the medical device and the ~~simulated body cavity or lumen~~ in three-dimensions, computes forces that would arise from interactions between the medical device and ~~the simulated body cavity or lumen~~ and feeds back ~~signals to the interface device so as to thereby feedback~~ said forces to the first user via the medical device; and

_____ (d) _____ at least one first display device being operably coupled to the computational engine and for displaying a three-dimensional representation of the ~~simulated body cavity or lumen and a three-dimensional representation of the medical device within the simulated body cavity or lumen;~~ wherein the computational engine further simulates movement of the medical device within the simulated body cavity or lumen in real-time as the first user manipulates the medical device within the simulated body cavity or lumen and causes such simulations to be displayed on the first display device.

75. (Currently Amended) A simulator system comprising a simulacrum and a medical device, ~~the simulator system for simulating use and movement of the a~~ medical device in a body cavity or lumen of a patient; and further comprising:

(a) ~~a the~~ medical device having comprising a first end for manipulation by a first user and a portion including comprising a second end insertable into ~~a the~~ simulated body cavity or body lumen in ~~a the simulacrum; manikin;~~

- (b) ~~the simulacrum a manikin including comprising an interface device configured to receive for receiving the portion including comprising the second end and to interface for interfacing with the a simulated body cavity or lumen; within the manikin; and~~
- (c) a processor for simulating real-time movement of the medical device with ~~a the simulated body cavity or lumen as the first user manipulates the medical device,~~ wherein deformation of the simulated body cavity or lumen in response to blood flow or the movement of the medical device is modeled using physically based modeling ~~embodying that uses finite element methodology in real-time and wherein the processor computes forces that would arise from interactions between the medical device and body cavity or lumen and provides a feedback signal to the interface device for simulating said forces to the first user; and~~
- (d) ~~at least one first display device being operably coupled to the processor engine and for displaying a three-dimensional representation of the simulated body cavity or lumen and a three-dimensional representation of the medical device within the simulated body cavity or lumen, wherein the processor causes the simulated real-time movement of the medical device within the simulated body cavity or lumen to be displayed on the first display device.~~

76. (Currently Amended) The ~~simulator system~~ according to any of claims 1, 74, or 75, wherein one of the computational engine or the processor alters a finite element structure corresponding to the medical device and/or body cavity or lumen ~~is altered~~ in response to a manipulation of the medical device by the ~~first user~~.

77. (Currently Amended) The simulator system according to any of claims 1, 74, 75, wherein:

the simulated body cavity or lumen is a simulated blood vessel of a vascular system; and the system models interactions, using said one of the computational engine or the processor, between the medical device and a wall of the blood vessel and computes forces that would arise from the interactions between the device and the vessel wall and feeds back signals to the interface device so as to thereby feed back such computed forces back to the first user.

78. (Currently Amended) The simulator system according to claim 77, wherein the one of the computational engine or the processor simulates a path that represents at least a portion of the vascular system and determines a fit between geomtery of the medical device and the geometry of the simulated path.

79. (Currently Amended) The simulator system of claim 77, wherein the blood vessel is modeled in the one of the computational engine or the processor as one of a rigid cylindrical body or a deformable structure strucutre to reflect a pathology of the blood vessel.

80. (Currently Amended) The simulator system of claim 77, wherein the system further includes modeling interactions between the medical device and flow of blood in the blood vessel.

81. (Currently Amended) The method according to claim 52, further ~~comprising~~comprises the step of; altering a finite element structure corresponding to the medical device and/or body cavity or lumen in response to a manipulation of the medical device by the first user.

82. (Currently Amended) The method of claim 52, wherein:

the simulated body cavity or luman is a simulated blood vessel of a simulated vascular system;

_____ said inserting includes inserting the portion of the provided medical device by the first user into the simulated blood vessel,

said performing physically based modeling includes performing physically based modeling to simulate interactions between the medical device and a wall of the simulated blood vessel; and

said computing forces includes computing forces that arise from interactions between the medical device and the simulated blood vessel.

83. (Currently Amended) The method of claim 82, wherein said performing physically based modeling includes simulating a path that represents at least a portion of the simulated vascular system and determining a fit between the geometry of the medical device and the geometry of the simulated path.

84. (Currently Amended) The method of claim 82, wherein said performing physically based modeling includes performing physically based modeling of the simulated blood vessel as one of a rigid cylindrical structure or a deformable structure to reflect a pathology ~~of the blood vessel~~.

85. (Currently Amended) The method of claim 82, further comprising:
modeling of interactions between the medical device and flow of blood in the simulated blood vessel and providing a feed back of such interactions to the first user via the medical device.

86. (Currently Amended) The simulator system according to claim 1, wherein:
the simulated body lumen is a simulated blood vessel of a simulated vascular system;
the computational engine embodying physically based modeling simulating interactions between the medical device and the simulated blood vessel; and

the system models interactions, using said computational engine, between the medical device and a wall of the simulated blood vessel and computes forces that would arise from the interactions between the medical device and the vessel wall and feeds back such computed forces back to the first user via the medical device.

87. (Currently Amended) The simulator system according to claim 86, wherein the medical device is selected from the group consisting of a catheter, guidewire, endoscope, laparoscope, bronchoscope, stent, coil, balloon, a balloon-inflating device, a surgical tool, a vascular occlusion device, optical probe, a drug delivery device, and combinations thereof.

88. (Currently Amended) The simulator system according to claim 7 wherein the tactile feedback mechanism provides a continuous oscillatory feedback to a first user holding the medical device to simulate medical device motion induced by simulated forces being exerted on the medical device by physiological paramters.

89. (Currently Amended) The method according to claim 63 wherein the tactile feedback mechanism provides a continuous oscillatory feedback to a first user holding the medical device to simulate medical device motion induced by simulated forces being exerted on the medical device by physiological paramters.